

Sandvik Ranger DX800I med følgende spesifikasjon.

Hydraulic crawler drilling rig, serial no xxxxx

Basic unit:

1 pc Rock drill RD925M, hydraulic with SLU system
1 pc CylF 18 feed HR, With hose reel
1 pc Rod handler RC1712 incl. 1 set of jaws
1 pc BoomDB5200, articulated
1 pc Carrier track mounted, Rotating upper structure CW180+CCW110 Degrees
1 pc Power pack diesel driven, hydraulic pumps and on-board compressor with twin pressure control
1 pc Control system ITorque, Incl Flushing control automatics, Shutdown of suction for waterholes
1 pc TIMI for vertical holes and depth measuring
1 pc Operator's cabin F.O.P.S. and R.O.P.S. with Intelligent air condition safety +
1 pc Radio, 12V with USB MP3 Bluetooth, without CD
1 pc Dust collection system DC 900 H, hydraulic, Primary separator
1 pc Shut down of suction in water holes
10 pcs Working lights, Halogen
1 pc Gauge set for accumulator pressure checking
1 pc Alarm signal
1 Set Manuals, paper copy
1 Set Manuals, USB memory
1 pc Alarm beacon
1 pc Service light
SanRemo Mobile, Bluetooth connectivity
EU-safety devices, EN16228

Site Info:

- Alternative drill steel – T45 (Ø45 mm) rods for Ø76 mm holes
- Altitude -- 1000 to 1500 meters above sea level
- Drill steel – Ø51 mm (2") rods / T51
- Drill steel type – MF-rods
- Flushing housing -- RD92x - 52
- Manual languages -- Norwegian
- Rotation motor – OMT400 for 89-115 mm holes

